



- NOTES:
1. UNLESS OTHERWISE SPECIFIED, ALL RESISTANCE VALUES ARE EXPRESSED IN OHMS; K=1,000 OHMS. ALL RESISTORS ARE ±10%, 1/4 W, UNLESS OTHERWISE SPECIFIED.
 2. UNLESS OTHERWISE SPECIFIED, ALL CAPACITANCE VALUES ARE EXPRESSED IN μF.
 3. CAPACITOR C12 IS NOT USED.
 4. LAST REFERENCE DESIGNATIONS ARE C19, CR8, L4, Q3, R18, AND T2.
 5. DC VALUES MEASURED WITH 11 MEG Ω INPUT IMPEDANCE VTVM.
 6. AC VALUES MEASURED WITH HIGH INPUT IMPEDANCE REF VTVM (BOONTON 91CA OR EQUIV)
 7. VAVEFORMS OBTAINED WITH 100MHZ OSCILLOSCOPE.
 8. SEE FIELD SERVICE MANUAL FOR LEVELS TO CHECK PRODUCT DETECTOR OPERATION USING AUDIO AMPLIFIERS.

4	3	2	1	QTY REQD PER GROUP	WARRANTY NUMBER	DESCRIPTION	REVISION	DATE
SOURCE CODE		UNLESS OTHERWISE STATED (CONTRACT NO)						
1 ST N.P.C.I.F.S.		DIMENSIONS ARE IN INCHES						
SC = VENDOR ITEM - SEE SOURCE		INCLUDING PLATING TOLERANCES						
OR S.P.C. CONTROL DWG		TOLERANCES ARE						
3D = N.P.C.I.F.S. BY		FRACTIONAL DIMENSIONS ARE IN						
		DECIMALS ARE IN						
		TOLERANCES ARE						
		TOLERANCES ARE						
		TOLERANCES ARE						